

Polyamide Toughened Conduits

- **Material :** Toughened polyamide 6 , RM UL-94 HB
 - **Ingress protection :** IP 68 With ends properly sealed or in combination with suitable glands
 - **Resistant :** Most chemicals & alkalies, good weathering properties
- UV Stabilised conduits available upon request on MOQ basis.
slitted conduits available on MOQ basis.

- **Tensile modules** : 17300 KGF/cm²
- **Flexural modules** : 8400 K²G/cm
- **Tensile strength** : 590 KG(F)²cm
- **Impact strength** : 20 KG(F)cm
- **Temperature range** : -10°C TO +90°C
- **Certification/Standard** : RoHS, CE, IEC 61386-1 / 61386-23

Customised colours available subject to MOQ / Charged 15% EXTRA

Flucon conduits are suitable for in various industries such as automation/railways/ under carriage/machine building etc



Part Code	Part Description	Conduit Size		Quantity Per Roll	Rolls per Master Bags	Master Bag Quantity	MRP Per Meter
		ID	OD				
		mm	mm	meter	rolls	meter	Rs.
FCFGNCP0009	FCNCP- 5 ID	5.1	7.6	200	3	600	45.00
FCFGNCP0010	FCNCP-7 ID	6.4	10	100	5	500	49.00
FCFGNCP0002	FCNCP-10 ID	9.60	13.00	50	10	500	50.00
FCFGNCP0004	FCNCP-12 ID	12.00	15.80	50	10	500	63.00
FCFGNCP0006	FCNCP-17 ID	16.20	21.20	50	6	300	88.00
FCFGNCP0008	FCNCP-23 ID	22.60	28.50	50	4	200	125.00
FCFGNCP0020	FCNCP-29 ID	29.00	34.50	50	3	150	150.00
FCFGNCP0012	FCNCP-36 ID	36.50	42.50	25	3	75	200.00
FCFGNCP0014	FCNCP-48 ID	47.50	54.50	25	2	50	285.00